



FIREHORSE

FULHAM



HIGH PERFORMANCE FLUORESCENT EMERGENCY LIGHTING BALLASTS

- WIDE RANGE OF LUMEN OUTPUT
- WIDE RANGE OF LAMP COMPATIBILITY
- WIDE RANGE OF BALLAST COMPATIBILITY
- LOW PROFILE FOR INTEGRAL MOUNTING
- FACTORY OR FIELD INSTALLATION
- 3- YEAR WARRANTY



FULHAM
Harness the Horsepower



FH4-DUAL-700L



- Initial Lumen Output - 700 Lumens
- Engineered for use with a wide range of CFL / U-shape / Circline / Long Compact and Linear Fluorescent Lamps
- LED Charge Indicator and Test Switch
- 3-year full warranty

Specifications

Initial Lumen Output	700
AC Input	3.5W
Charging Current	280mA Max.
Battery Voltage	3.6Vdc
Battery Rating	14.4Wh
Warranty	3 Years
Case Size	H 1.5" W 2.4" L 9.4" Ctr 8.9"
Ballast Weight	2.8 lbs
Case Quantity	1 pc
Master Carton Quantity	6 pcs

FireHorse Lamp Operation | **Also works with TLEDs.** Check lamp manufacturers' specifications for compatibility.

LAMP APPLICATIONS	FH4
FT - 4 pin	
FT36W	1 or 2
FT40W	1
FT50W	1
FT55W	1
CFTR - 4 pin	
CFTR57W	1
Circular-FCRT5	
22WCRT5	1 or 2
40WCRT5	1 or 2
55WCRT5	1
2D - 4 pin	
2D28W	1 or 2

LAMP APPLICATIONS	FH4
2D - 4 pin	
2D38W	1
2D55W	1
T5-Standard	
F21T5	1 or 2
F28T5	1
F35T5	1
T5-HO High Output	
F39T5HO	1
F54T5HO	1
T8- Standard	
F25T8	1 or 2
F32T8 (25W)	1 or 2
F32T8 (28W)	1 or 2
F32T8 (30W)	1 or 2
F32T8 (32W)	1 or 2
FB32T8	1 or 2
F32T8 ES (28W)	1 or 2
F51T8	1
F59T8	1

LAMP APPLICATIONS	FH4
T8-HO High Output	
F44T8HO	1
F86T8HO	1
T12-Standard	
F25T12	1 or 2
F30T12	1 or 2
FB34T12	1 or 2
F40T12	1 or 2
F40T12 ES (34W)	1 or 2
F75T12, F85T12	1
F85T12	1