





## **HotSpot1 LED Emergency Lighting Kits**



- Quick plug-n-play room-side installation
- Revolutionary design for extreme versatility
- UNV and many battery options for superior adaptability
- High efficiency, high lumen output LEDs for cost effectiveness

Fulham's HotSpot1 kits provide easy-to-install emergency LED lighting for common troffer installations, including T5 and T8 LED tube retrofits. They are UL Classified for field or factory installation, with a range of battery and module options to fit any situation. Each kit includes a HotSpot1 emergency LED driver, battery pack, LED module, required hardware, the necessary UL Classified label (to secure to the fixture after installation), and complete installation instructions.



## HotSpot1 UL Classified Kits for Troffers



HotSpot1 kits for troffers include an emergency driver, battery, LED module, installation instructions, and all necessary hardware and labels. The kits are not electrically connected to the normal lumination source. Choose the right kit for the job according to the required lumen output, run time, and module dimensions. Contact Fulham for details.

| Common Specifications   |                 |                                 |                    |  |  |  |  |  |
|-------------------------|-----------------|---------------------------------|--------------------|--|--|--|--|--|
| Input Voltage           | 120V-277V (UNV) | Output Short Circuit Protection | Self Resetting PTC |  |  |  |  |  |
| Surge Protection        | C62.41 (TVS)    | Recharge Time Required          | 24 hours           |  |  |  |  |  |
| Over Current Protection | Fuse            | Battery Type                    | NiCd 3.6VDC        |  |  |  |  |  |
| Input Current           | 0.07A           | Illumination Time               | Minimum 90 minutes |  |  |  |  |  |
| Input Power             | <4W             | Output Classification           | UL 1310 / Class 2  |  |  |  |  |  |
| Output Voltage          | 3.6V            | Ambient Temperature             | 0°C - 50°C         |  |  |  |  |  |

| UL Classified Kits |       |              |                    |             |                         |
|--------------------|-------|--------------|--------------------|-------------|-------------------------|
| Model Number       | Watts | Lumen Output | Estimated Run Time | Module Type | Module Dimensions (LxW) |
| FHSKITT03LNC       | 3     | 450          | 145 Mins           | Linear      | 4.68" x 0.82"           |
| FHSKITT03LND       | 3     | 450          | 200 Mins           | Linear      | 4.68" x 0.82"           |
| FHSKITT03LNF       | 3     | 450          | 360 Mins           | Linear      | 4.68" x 0.82"           |
| FHSKITT03LNFL†     | 3     | 450          | 360 Mins           | Linear      | 4.68" x 0.82"           |
| FHSKITT04LNC       | 4     | 500          | 145 Mins           | Linear      | 4.68" x 0.82"           |
| FHSKITT04LND       | 4     | 500          | 200 Mins           | Linear      | 4.68" x 0.82"           |
| FHSKITT04LNF       | 4     | 500          | 360 Mins           | Linear      | 4.68" x 0.82"           |
| FHSKITT06SHC       | 6     | 750          | 90 Mins            | Small-H     | 3.54" x 3.93"           |
| FHSKITT06SHD       | 6     | 750          | 125 Mins           | Small-H     | 3.54" x 3.93"           |
| FHSKITT06SHF       | 6     | 750          | 235 Mins           | Small-H     | 3.54" x 3.93"           |
| FHSKITT07LND*      | 7     | 900          | 100 Mins           | Linear      | 4.68" x 0.82"           |
| FHSKITT07LNF*      | 7     | 900          | 180 Mins           | Linear      | 4.68" x 0.82"           |
| FHSKITT07LNFL*†    | 7     | 900          | 180 Mins           | Linear      | 4.68" x 0.82"           |
| FHSKITT08LHD       | 8     | 1000         | 90 Mins            | Large-H     | 5.71" x 3.93"           |
| FHSKITT08LHF       | 8     | 1000         | 175 Mins           | Large-H     | 5.71" x 3.93"           |
| FHSKITT10LHF       | 10    | 1250         | 135 Mins           | Large-H     | 5.71" x 3.93"           |
| FHSKITT10SHF       | 10    | 1250         | 135 Mins           | Small-H     | 3.54" x 3.93"           |
| FHSKITT10LNF**     | 10    | 1350         | 120 Mins           | Linear      | 4.68" x 0.82"           |
| FHSKITT10LNFL**†   | 10    | 1350         | 120 Mins           | Linear      | 4.68" x 0.82"           |

<sup>\*</sup>Includes 2 linkable 450lm linear modules

†Linear Battery



<sup>\*\*</sup> Includes 3 linkable 450lm linear modules