


## TECHNICAL DATA SHEET: ELECTRONIC BALLAST

Project : STANDARD Type : PROFESSIONAL

Model No : HPY-240-236-IT8-OAE Remark :



Input Characteristics				
1	Voltage (Un)	240 Vac		
2	Operating Voltage Range	140 ~ 277 Vac		
3	Frequency (Hz)	50 / 60 Hz		
4	Current (A)	0.31 A		
5	Wattage (W)	72W		
6	Power Factor (PF)	> 0.97 (PPFC)		
7	Current Harmonics (Athd)	< 20%		
8	Over Current Protection	Yes		
9	Surge Withstanding Capacity	Yes		
10	Over Voltage Application	@ 320Vac 48Hrs & @ 360Vac 2 Hrs		

Output Characteristics				
1	Lamp Types	36W-T8-FTL 40W-T12-FTL 36W-PLL		
2	Number of Lamps	2		
3	Lamp Connection	Dual Series		
4	Single Lamp Operation	No		
5	Lamp Current	0.320A		
6	Operating Frequency	> 40 KHz		
7	Ignition Method	RS		
hara	haracteristics			
1	Lamp Current Crest Factor (CCF)	<u>&lt;</u> 1.70		
2	Ballast Efficiency (BE)	<u>&gt;</u> 86%		
Protection Features				
1	Deactivated Lamp	Yes		
2	Restart or Latching	Latching		

	Mechanical Details				
1	Weight	160 gm			
2	Case Dimensions				
	Length W/Mount	282 mm			
	Center to Center ( CTC )	272 mm			
	Width	24 mm			
1	Height	21 mm			
3	Case Material	Metal Case			
4	Wiring Diagram	On Screen			
5	Input / Output Connections	Connectors Push Type			
6	Wires Length & Colors				
	Input ( White & Black )	N/A			
	Output ( White )	N/A			
	Output ( Gray )	N/A			
7	Potting	N/A			

Environmental Operating Details			
1	Minimum Lamp Starting Temperature	0°C	
2	Max. Ambient Temperature	50°C	
3	Max. Case Temperature (Tc)	75°C	

Ordering Information				
Sr	Model Number	Description	Case Lot	
1	HPY-240-236-IT8-OAE	2x36W T8 <20% THD 2x40W T12 <20% THD 2x36W PLL <20% THD	50	

## Note

A High power factor Electronic ballast specially designed for heavy duty use.

## Key features :-

- Slim Design
- High Voltage withstanding capacity.
- High Surge withstanding capacity
- Long Life.
- High Durability
- Lamp will not Shut down @ high Voltage
- Automatic restart after lamp replacement

Fulham extends a limited warranty only to the original purchaser or to the first user for a period of 2 years from the date of manufacture when properly installed and operated under normal conditions of use. For complete terms and conditions, please reference the Fulham product catalog

Due to a program of continuous improvement, Fulham reserves the right to make modifications or variations in design or construction to the equipment described. © Fulham Company Limited, All Rights Reserved.

DOC NUMBER :-FULTDS024

Date :-01.04.2013