FULHAM.

"AT A GLANCE"



Tri-Dim; 0-10V, ELV and TRIAC

65W in a compact case form factor

Field Programmable - 300-1800mA



coming soon



Specialty Applications Include:
Refrigeration
Signage, Cove, Mirror,
Landscaping,
Decorative, Flex
Tape/Linear Runs

Constant Voltage (CV) 12V and 24V Dimmable and Non-dimmable versions







(WHSG) OUTDOOR PROGRAMMABLE DRIVERS

Non-Class 2 LED Drivers (75W-320W) with Multiple Options per Wattage (Different Output Current & Voltage)

IP66, Type HL, high input surge (6kV/10kV), Dry & Damp Rated, 0-10V Dimming

Field Programmable on a wide range of output current with TPSB-100



coming soon

FULHAM.

"AT A GLANCE"



Versatility and Convenience via 7 models that cover 300 - 1300mA (Vf 30-42V)

CURRENT LED DRIVERS

3 Selectable Preset Currents per model via a dip switch

Cost Effective Solution with NO need for a programming tool





(THCC) Programmable Indoor LED Drivers

The power to create the right driver for any situation: 30W, 50W, 85W

Wide programmable current range across 3 models (350-2400mA)

Field-programmable with handheld programmer TPSB-100





(WHCC) Programmable Outdoor LED Drivers

Small form factors with extruded aluminum design for thermal performance

Type HL, high input surge (6kV/10kV), IP65/66

Field Programmable with handheld programmer TPSB-100 (350-2670mA)

