

Specifcation Sheet: FHNY22 Series

Model: FHNY22

Project:	Type:	Model No.:
,	, ————	

Remarks:

Specifcations:

Lamp Type	LED
Emergency Operation	90 minutes

Listings & Certifications:







Standard Features:

- Push-To-Test Switch
- LED Charge Indicator
- Maintenance Free, 6V Sealed Ni-Cd Battery
- Dual Voltage 120V/277V
- Specification Grade Design
- Universal Mount
- Graduated Depth of Molded Letters Provides Uniform Light Distribution on Graphics
- Long Life Energy Saving Led Light Source
- · AC and EM Models
- Field Applied Chevron Directional Indicators
- High-Polish, Injection-Molded Virgin Acrylic Panel, Ultrasonically Welded to Eliminate Visible Hardware
- Mirror Divider on Double Face Versions
- · New York City Approved

Mechanical Data: 25" 13" 14.5" 17.4"

Ordering Information:

Base Model No.	Case Color	Number of Faces	Operation	Options
FHNY22 W - White B - Black	A - Aluminum	S - Single	AC - AC Only	
		7.0 7.0 0,	SD - Self Diagnostic	
	B - Black	D - Double	EM - Battery Backup	

Build part number by adding Base Model No., one of each Case Color, Number of Faces, Operation and desired options code(s). Example: FHNY22-A-S-EM-SD