



Specification Sheet : T5 Lamps

Project: _____ Type: _____ Model No.: _____

Remarks: _____

Model: T5



Lamp Specifications:

Fluorescent T5 Linear Mini Bipin Lamps.

1. Custom colors (CCT) are available, 27k thru 65k, As special order, call 1-323-599-5000.

*Rated lamp life based on 3 hours per start (min.).

Lamp Data:

Nominal Wattage	CCFL Bulb	MOL	MOL	Item Number	NEMA Generic Description	Pkg Qty	Rated Life	Rated Life*	CCT (K)	CRI	Approx. Lumens	Approx. Lumens
		(in)	(mm)								Initial	Mean
8	T5	11.909	302.5	FLFT58W827	F8T5	25	5000	N/A	2700	≥ 82	460	430
8	T5	11.909	302.5	FLFT58W835	F8T5	25	5000	N/A	3500	≥ 82	460	430
8	T5	11.909	302.5	FLFT58W841	F8T5	25	5000	N/A	4100	≥ 82	460	430
8	T5	11.909	302.5	FLFT58W865	F8T5	25	5000	N/A	6500	≥ 82	460	430
13	T5	20.909	531.1	FLFT513W827	F13T5	25	7500	N/A	2700	≥ 82	960	880
13	T5	20.909	531.1	FLFT513W841	F13T5	25	7500	N/A	4100	≥ 82	960	880
14	T5	22.173	563.2	FLFT514W827	F14T5	25	20000	35000	2700	≥ 82	1350	1230
14	T5	22.173	563.2	FLFT514W830	F14T5	25	20000	35000	3000	≥ 82	1350	1230
14	T5	22.173	563.2	FLFT514W835	F14T5	25	20000	35000	3500	≥ 82	1350	1230
14	T5	22.173	563.2	FLFT514W841	F14T5	25	20000	35000	4100	≥ 82	1350	1230
14	T5	22.173	563.2	FLFT514W850	F14T5	25	20000	35000	5000	≥ 82	1350	1230
14	T5	22.173	563.2	FLFT514W865	F14T5	25	20000	35000	6500	≥ 82	1350	1230
21	T5	33.984	863.2	FLFT521W827	F21T5	25	20000	35000	2700	≥ 82	2100	1910
21	T5	33.984	863.2	FLFT521W830	F21T5	25	20000	35000	3000	≥ 82	2100	1910
21	T5	33.984	863.2	FLFT521W835	F21T5	25	20000	35000	3500	≥ 82	2100	1910
21	T5	33.984	863.2	FLFT521W841	F21T5	25	20000	35000	4100	≥ 82	2100	1910
21	T5	33.984	863.2	FLFT521W850	F21T5	25	20000	35000	5000	≥ 82	2100	1910
21	T5	33.984	863.2	FLFT521W865	F21T5	25	20000	35000	6500	≥ 82	2100	1910
28	T5	45.795	1163.2	FLFT528W827	F28T5	25	20000	35000	2700	≥ 82	2900	2640
28	T5	45.795	1163.2	FLFT528W830	F28T5	25	20000	35000	3000	≥ 82	2900	2640
28	T5	45.795	1163.2	FLFT528W835	F28T5	25	20000	35000	3500	≥ 82	2900	2640
28	T5	45.795	1163.2	FLFT528W841	F28T5	25	20000	35000	4100	≥ 82	2900	2640
28	T5	45.795	1163.2	FLFT528W850	F28T5	25	20000	35000	5000	≥ 82	2900	2640
28	T5	45.795	1163.2	FLFT528W865	F28T5	25	20000	35000	6500	≥ 82	2900	2640
35	T5	57.6	1463.0	FLFT535W827	F35T5	25	20000	35000	2700	≥ 82	3650	3300
35	T5	57.6	1463.0	FLFT535W830	F35T5	25	20000	35000	3000	≥ 82	3650	3300
35	T5	57.6	1463.0	FLFT535W835	F35T5	25	20000	35000	3500	≥ 82	3650	3300
35	T5	57.6	1463.0	FLFT535W841	F35T5	25	20000	35000	4100	≥ 82	3650	3300
35	T5	57.6	1463.0	FLFT535W850	F35T5	25	20000	35000	5000	≥ 82	3650	3300
35	T5	57.6	1463.0	FLFT535W865	F35T5	25	20000	35000	6500	≥ 82	3650	3300

This Is An Original Product From Fulham Co., Inc. Due to a program of continuous improvement, Fulham Co., Inc. reserves the right to make any variation in design or construction to the equipment described.



Specification Sheet : T5-HO Lamps

Project: _____ Type: _____ Model No.: _____

Remarks: _____

Model: T5 High Output



Lamp Specifications:

Fluorescent T5 High Output Linear Mini Bipin Lamps.

1. Custom colors (CCT) are available, 27k thru 65k, As special order, call 1-323-599-5000.

*Rated lamp life based on 3 hours per start (min.).

Lamp Features:

- High Output T5 Lamp
 - Full Range of Color Temperatures (CCT)
 - High Color Rendering Index (CRI) ≥ 82
 - Longer Rated Life 35,000 Hours
 - TCLP Compliant, Lowering Disposal Costs Where Applicable (State Regulations Vary, Consult Your State EPA).
- Variety of Application Including:
 1. Fluorescent HighBay Fixtures
 2. Warehouse Fixtures
 3. Retail Lighting

Lamp Data:

Nominal Wattage	CCFL Bulb	MOL	MOL	Item Number	NEMA Generic Description	Pkg Qty	Rated Life	Rated Life*	CCT (K)	CRI	Approx. Lumens	Approx. Lumens
		(in)	(mm)				3 hrs	12 hrs			Initial	Mean
24	T5	22.173	563.2	FLFT5EH24W830	F24T5-HO	25	20000	35000	3000	≥ 82	2000	1750
24	T5	22.173	563.2	FLFT5EH24W835	F24T5-HO	25	20000	35000	3500	≥ 82	2000	1750
24	T5	22.173	563.2	FLFT5EH24W841	F24T5-HO	25	20000	35000	4100	≥ 82	2000	1750
24	T5	22.173	563.2	FLFT5EH24W850	F24T5-HO	25	20000	35000	5000	≥ 82	2000	1750
24	T5	22.173	563.2	FLFT5EH24W865	F24T5-HO	25	20000	35000	6500	≥ 82	2000	1750
39	T5	33.984	863.2	FLFT5EH39W830	F39T5-HO	25	20000	35000	3000	≥ 82	3500	3200
39	T5	33.984	863.2	FLFT5EH39W835	F39T5-HO	25	20000	35000	3500	≥ 82	3500	3200
39	T5	33.983	863.2	FLFT5EH39W841	F39T5-HO	25	20000	35000	4100	≥ 82	3500	3200
39	T5	33.983	863.2	FLFT5EH39W850	F39T5-HO	25	20000	35000	5000	≥ 82	3500	3200
39	T5	33.983	863.2	FLFT5EH39W865	F39T5-HO	25	20000	35000	6500	≥ 82	3500	3200
54	T5	45.795	1163.2	FLFT5EH54W830	F54T5-HO	25	20000	35000	3000	≥ 82	5000	4460
54	T5	45.795	1163.2	FLFT5EH54W835	F54T5-HO	25	20000	35000	3500	≥ 82	5000	4460
54	T5	45.795	1163.2	FLFT5EH54W841	F54T5-HO	25	20000	35000	4100	≥ 82	5000	4460
54	T5	45.795	1163.2	FLFT5EH54W850	F54T5-HO	25	20000	35000	5000	≥ 82	5000	4460
54	T5	45.795	1163.2	FLFT5EH54W865	F54T5-HO	25	20000	35000	6500	≥ 82	5000	4460

Measurements:



Notes:

LAMP CONTAINS MERCURY
 Manage in accordance with disposal laws.
www.lamprecycle.org or 800-555-0050



Because all fluorescent lamps contain mercury for effective operation, Fulham encourages proper lamp disposal for assurance of environmental protection.

This Is An Original Product From Fulham Co., Inc. Due to a program of continuous improvement, Fulham Co., Inc. reserves the right to make any variation in design or construction to the equipment described.